

## 1. Product Description

Product description	: SOMAFIX S80 MULTI USE PRODUCT is an aerosol spray with high penetration ability that lubricates, loosens and polishes moving rusted parts. It provides protection against rust and corrosion in household and industrial applications
Use of the substance/mixture	: Rust Remover and Lubricating Spray
Recommended use	: Industrial use Professional uses Consumer use

## 2. Characteristics

Characteristics	: Has high penetration ability  Provides protection against moisture and rust by forming a protective film layer on the surface  Do not form a dirt layer on the surface because of not containing any additive material as silicone or dust and dirt collector
-----------------	---

## 3. Application

- Loosens all fittings, nuts, bolts, chain wheels, roller, bicycle gears and jammed door locks, protects from rust and polishes
- Removes moisture in flooded equipments such as engine parts, engine, spark plug, electrical and hand tools.
- Completely removes grease oil and dirt, stickers and adhesive residues from the surface
- Removes rust from rusted surfaces
- Removes abrasion from jammed nuts, connections, control mechanisms, and other metal parts

## 4. Application Instructions

- Application temperature is between -10 ° C and +45 ° C
- Shake the container well before use
- Hold the container vertically and spray it on the application area
- If the application area is cleaned, it will increase the spray effect
- Wait for penetrating to the surface
- Clean with brush after application

## 5. Technical Specifications (@ 23 °C 50% RH)

Basis	: Solvent mixture.
Colour	: Light amber
Odour	: characteristic
Density	: 0.79 – 0.81 g/cm <sup>3</sup>
Flash point	: Not applicable, as aerosol. (≤50°C)
Application Temperature	: -10 → 45 °C
Solubility in water	: Insoluble

## 6. Packaging

**Packaging** : Aerosol.

Canister 200 ml	Package 24 pcs/ctn
Canister 350 ml	Package 24 pcs/ctn
Canister 400 ml	Package 24 pcs/ctn

## 7. Shelf Life and Storage

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool. Store locked up.

Storage temperature : -10 → 35 °C

Canister 200 ml	36 months (after production date if stored at room temperature.)
Canister 350 ml	36 months (after production date if stored at room temperature.)
Canister 400 ml	36 months (after production date if stored at room temperature.)

## 8. Health and Safety

Adverse physicochemical, human health and environmental effects	: Pressurised container: May burst if heated. Extremely flammable aerosol. Causes skin irritation.
First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after ingestion	: Risk of lung oedema.
Other medical advice or treatment	: Treat symptomatically.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. [In case of inadequate ventilation] wear respiratory protection.

## 9. Remarks

Remarks : For further information, please refer to the Safety Data Sheet

## 10. Standards and Certificates

No information available

Technical Data Sheet

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*